

CO2 EXTINGUISHER

GENERAL

GFIRE CO2 fire extinguishers leave no residue after discharge, therefore they are ideal for B and electrical fire risks involving electrical equipment's in residential, commercial and industrial environments like computer rooms, data storage centres etc.

FEATURES

- Designed and approved to EN3
- Clean with no harm to machinery equipment's
- High UV resistant polyester coating for extra protection from extremely harsh elements
- Chrome plated valve with pressure release mechanism
- Fitted with anti-electrostatic hose & horn for effective discharge
- Complete with metal wall brackets. Heavy duty brackets for marine and truck applications are optional



TECHNICAL DATA

Model	GF-CD2	GF-CD2A	GF-CD5	GF-CD5A
Body Material	Steel	Aluminium	Steel	Aluminium
Extinguishing Medium	Co2	Co2	Co2	Co2
Capacity (Kg)	2	2	5	5
Height(mm)	565	545	745	675
Shell Diameter(mm)	103	111	136	152
Working Pressure(bar)			150	
Test Pressure(bar)			250	
Full Weight(kg)	6.20	5.00	14.40	12.00
Discharge Time Approx.(second)	6	6	9	9
Temperature Range			-30°C - +60°C	
Fire Rating	34B	34B	70B	70B

