

FOAM EXTINGUISHER

GENERAL

GFIRE Foam fire extinguishers provide a cleaner and also same effective alternative to dry powder extinguishers for class A and B fire risks

FEATURES

- Designed and approved to EN3
- All models are tested to clause 9.2 of EN3-7 for use on Live electrical equipment's
- High UV resistant polyester coating for extra protection from extremely harsh elements
- Polyethylene lined cylinders for corrosion resistance
- Easy squeeze-grip operation and all metal handles
- Complete with metal brackets (2Litre models with vehicle brackets)
- Heavy duty brackets for marine and truck applications are optional



TECHNICAL DATA

Model	GF-FM2S	GF-FM3S	GF-FM6S	GF-FM9S
Propellant type	Stored Pressure			
Extinguishing Medium	AFFF Foam	AFFF Foam	AFFF Foam	AFFF Foam
Capacity (Kg)	2	3	6	9
Height(mm)	403	438	537	620
Shell Diameter(mm)	110	130	162	182
Working Pressure(bar)				15
Test Pressure(bar)				27
Full Weight(kg)	3.60	5.20	9.60	14.00
Discharge Time Approx.(second)	15	20	22	30
Temperature Range	5°C - +60°C			
Fire Rating	8A 55B	13A 89B	21A 183B	27A 233B

