

WATER EXTINGUISHER

GENERAL

GFIRE Water fire extinguishers is a cost effective option for class A fire risk only

GFIRE Water ADDITNE fire extinguishers radically increase the effectiveness of a water fire extinguisher by up to 300%, as well as reducing the size of extinguisher required

FEATURES

- Designed and approved to EN3
- All models except TMWT9 are tested to clause 9.2 of EN3-7 for use on live electrical equipment's
- High UV resistant polyester coating for extra protection from extremely harsh elements
- Polyethylene lined cylinders for corrosion resistance
- Easy squeeze- grip operation and all metal handles
- Complete with metal brackets



TECHNICAL DATA

Model	GF-WT6	GF-WT9	GF-WT3A	GF-WT6A
Propellant type	Stored Pressure			
Extinguishing Medium	Water	Water	Water Additive	Water Additive
Capacity (Kg)	6	9	3	6
Height(mm)	537	620	435	537
Shell Diameter(mm)	162	182	130	162
Working Pressure(bar)	15			
Test Pressure(bar)	27			
Full Weight(kg)	9.60	14.00	5.20	9.60
Discharge Time Approx.(second)	45	22(Jet Nozzle)	20	45
Temperature Range	5°C - +60°C			
Fire Rating	13A	21A	13A	27A

